



## BASKET TYPE STRAINER

These strainers can be offered in Simplex, Duplex type depending on your process requirements. The Duplex strainers are offered with diverting valves. These strainers are offered with flush, drain connections with ball valves as the standard feature. These strainers can be offered with various automats considering the process requirements. Our range of duplex filter are used wherever continuous operation is required and flow not to be interrupted. These duplex filter consist of two filtration chambers each rated for 100 %capacity. Basket Strainers can be offered with PERMANENT MAGNETS, which will separate magnetic dust from the liquids easily.



## SPECIFICATIONS :

<b>Material of Wetted Parts</b>	:	CI / ASTM A216 Gr WCB / ASTM A351 CF8 / ASTM A351 CF8M / MS / CS / SS304 / SS304L / SS316 / SS316L / PP & HDPE
<b>Filter Elements</b>	:	SS316 / SS304 / BRASS
<b>Mesh Size</b>	:	5 to 500 microns
<b>Temperature</b>	:	Up to 600°C
<b>Pressure</b>	:	Up to 60 Kg/CM <sup>2</sup>
<b>Line Size</b>	:	Up to 1200 NB depending upon the type
<b>Connection</b>	:	Flanged to ASA / BS / DIN / JIS / Screwed BSP / NPT / Butt Weld

