



WAFER BUTTERFLY VALVE

Butterfly valves suitable for simple as well as highly complex ones. Our Butterfly valves are rubber lined, PTFE lined. Butterfly valves are suitable as either open/closed or rare application in regulating valves. They are available in a wide variety of sizes, materials and models. Butterfly valves can be operated with various controls actions like electric / pneumatic actuator options.



SPECIFICATIONS :

BODY:	IS 210 GR FG 200 /220 / CS ASTM 216 GR WCB / SG IRON / SS 304 / SS 316
DISC:	IS 210 GR FG 200 / 220/CS ASTM 216 GR WCB / SG IRON / SS 304 / SS 316
SEAT:	MOUDED / REPLACEABLE NITRILE / EPDM / SILICON / VITON / HYPOLON / PFA / PTFE
SHAFT:	AISI 410 / AISI 304 / AISI 316
MFG STD:	BS 5155 / API 609 / ISO 5752
INSP &TEST STD:	BS 6755 / BS 5155
OPERATION:	FLOW CONTROL LEVER / GEAR OPERATED / PNEUMATIC ACTUATOR / ELECTRIC ACTUATOR
ENDS:	WAFER TYPE TO SUIT ANSI B 16.1
HYD TEST PRESSRE:	BODY : 225 PSIG (16 KG/CM2) SEAT : 165 PSIG (11.5 KG/CM2)
SIZE RANGE:	25 NB TO 1500 NB (1" to 60")

